




接触螺钉


中文版 09-07

接触螺钉，圆顶



用于标称油缸 ØD	a	b	c	R	SW	型号
12	M5	9	19	20	8	3614-027
16	M6	10	20	20	10	3614-016
12/16	M6	6	9.5	20	10	●3614-039
25	M8	10	20	20	11	3614-001
25	M10	12	22	35	17	3614-002
20/25	M8	8	13	25	13	●3614-038
32/40	M12	12	22	45	19	3614-028
40	M16	20	30	60	24	3614-003
50	M20	25	35	60	30	3614-015
63	M27	30	47	100	41	3614-017
80	M30	35	54	100	46	3614-018
100	M42	45	71	140	65	3614-019
125	M48	60	90	250	75	3614-020


●不会变硬，用于 B1.460



接触螺钉，锥形顶


用于标称油缸 ØD	a	b	c	α°	SW	型号
12	M5	9	16	120	8	3614-033
12/16	M6	6	18	90	10	*3614-068
16	M6	10	22	90	10	3614-032
20/25	M8	8	22	90	13	3614-069
25	M10	12	27	90	17	3614-021
32	M12	12	25	120	19	3614-031
40	M16	20	35	120	24	3614-022
50	M20	25	40	120	30	3614-023
63	M27	30	50	120	31	3614-024

*用于 B1.460




带联结销的接触螺钉，最大工作压力,牵引力 350bar

用于标称油缸 ØD	a	b	c	Ød	Øe	f	g	h	r	R	SW	型号
25	M10	14.5	32	20	10	12	6.5	5.5	1	320	17	3614-070
32	M12	14.5	32	20	10	12	6.5	5.5	1	320	17	3614-091
40	M16	20	40	25	14	14	7	6	1.5	400	22	3614-236
50	M20	28	56	33.2	17	22	10	10	1.5	500	27	3614-237
63	M27	39	75	40	23	32	13	12	2	630	36	3614-065
80	M30	35	89	52	28	25	19	19	2.5	800	46	3614-066



旋转接触螺钉，平面

最大载荷[KN]	用于标称油缸 ØD	a	b	c±0.02	Ød	Øe	SW	型号
10	12/16	M6	6	13	7.2	13	11	3614-228
10	20/25	M8	8	13	7.2	13	11	3614-072
25	25	M10	10	18	10.5	20	17	3614-073
25	32/40	M12	12	18	10.5	20	17	3614-074
90	40	M16	16	27	20	30	27	3614-075



旋转接触螺钉，锯齿面

最大载荷[KN]	用于标称油缸 ØD	a	b	c±0.1	Ød	Øe	SW	型号
10	20/25	M8	8	13	7.2	13	11	3614-131
25	25	M10	10	18	10.5	20	17	3614-194
25	32/40	M12	12	18	10.5	20	17	3614-118
90	40	M16	16	27	20	30	27	3614-119