

# Enhance the productivity of your company

## ■ SPEEDY module plates – for efficient setting-up

### Module plate start set, with overpressure release, order no. 803710

				
Hole gauge: 200 mm Insertion force: 2x 10'000 N Operating pressure: 80 bar Dimensions: 340 x 188 x 45 mm				
Consisting of:	<b>804 209</b>	<b>931 059</b>	<b>704 020</b>	<b>803 411</b>
Module plate double SPEEDY 10 kN	Retractable nipple with zero point	Cyl. head screw M12x40	Washer	Footpump, system pressure 80 bar air pressure max. 6 bar

### Module plate extension set, order no. 803 711

				
Hole gauge: 200 mm Insertion force: 2x 10'000 N Operating pressure: 80 bar Dimensions: 340 x 188 x 45 mm				
Consisting of:	<b>931 059</b>	<b>704 020</b>	<b>804 392</b>	<b>P00036</b>
Module plate double SPEEDY 10 kN	Cyl. head screw M12x40	Washer	Swivel screw connector <b>804 369</b> Swivel screw connector	MS-Pipe Ø 4/6x80

### Module plate accessories

					
<b>804 209</b>	<b>804 230</b>	<b>804 238</b>	<b>804 259</b>	<b>704 161</b>	<b>804 255</b>
Retractable nipple with zero point	Retractable nipple with balancer	Retractable nipple without centering	Positioning pin	Slidingblock with pin	Torque wrench
					<b>804 257</b> Socket
					
<b>804 254</b>	<b>804 368</b>	<b>803 790</b>	<b>803 791</b>		
Retractable nipple key	Coupling	Rupture plug	Nut for T-slot M12x14		